



(800) 513-9373 • (910) 342-0445 • Fax: (910) 342-0447  
P. O. Box 1259 • Wilmington, NC 28402

## INNOVATIVE OVER THE ROAD DROP CENTER CHIP TRAILER - DCS-48

<b>Capacity:</b>	3,834 cubic feet (142 cubic yards)(19.1 units), water level.
<b>Weight:</b>	<b>Approximately 11,188 lbs. +/- 3%.</b>
<b>Dimensions:</b>	48' Length, 102" Width, 13'6" Height (based on 50" Fifth Wheel height), 36" Rear Axle location, 37" King Pin setting, 42'1" King Pin to Rear Axle, 35' Landing Gear to Dump Blade, and 18" Ground Clearance.

- Side Walls:** .063 stressed aluminum mill finished skins, with exterior 6061-T6 aluminum aero posts on 21 1/2" center with 1/4" diameter sidewall rivets on 4 1/2" centers.  
**Heavy-duty side posts in drop area.**
- Top:** Open Top, single center tie design with front and rear diagonal bracing with aluminum top rail gussets.
- Front:** 45-degree front corners with interior front posts.
- Floor:** .063 corrugated aluminum "V-Groove".
- Rear Door:** Side hinge, skinned with expandable metal.
- King Pin:** Standard SAE heat-treated, 37" setting.
- Landing Gear:** Binkley Contender with 3" heavy-duty channel bracing with reinforced lugs for loaded set out. Crank on driver's side. Bally reinforced for dumping.
- Sub Frame:** Hutch 8800 fixed tandem with full welded construction.
- Cross Sills:** 4" x 3.2 lb./ft., 80,000 p.s.i. high strength steel, Jr. I-beams on 19" centers.
- Bumper:** ICC chip style, dump blade for end dump operation.
- Suspension:** Hutch CH9700 (cast) tandem, three leaf high arch, heavy duty springs, with no hop option.
- Axles:** 71 1/2" track, 22,500 lb. capacity, 5" round, hub piloted hubs with outboard drums, quick change brake shoes, and auto slack adjusters.
- Brakes:** 16 1/2" x 7", "Q" series, 4515 ED, non-asbestos lining, type 3030 air chambers, DOT Rockwell WABCO 2S/1M (2 Sensor/1 modular) ABS with dump valve.

- Tires & Wheels:** (8) 11R22.5 Bridgestone R194 radial tires. (8) 8.25 x 22.5 – 10 hole, hub piloted steel wheels.
- Tarp:** **Shur-Lok roll tarp with caps, bows and roll ground crank plus ratchet and straps.**
- Ladders:** Aluminum (1) located at front with safety loop and (1) ladder located at rear.
- Mud Flaps:** Legal rubber.
- Lights:** **(9) sealed lamps recessed in bumper** with Truck-Lite unitized wiring harness, 12 volt. Legal DOT.
- Reflectors:** Legal DOT reflective tape.
- Paint:** Aluminum natural, steel components sand blasted, primed and painted silver mist.

This offer may be withdrawn if not accepted within 30 days. Prices do not include Highway Use Tax, Federal, State, and Local Sales Taxes unless specifically stated above. Standard specifications are subject to change without prior notice.

**Acceptance of Proposal:**

For: Pinnacle Trailer Sales	For: _____
By: _____	By: _____
Date: _____	Date: _____

To accept this proposal, please sign where indicated and fax or send a copy of entire proposal back to Pinnacle Trailer Sales, Inc. fax (910)-342-0447. Thank you for your consideration.